

• High Pressure Cleaners • Steam Generators • Boilers

ALBERTI
INTERNATIONAL

STARJET 200

ALBERTI[®]
INTERNATIONAL

ALBERTI[®]

INTERNATIONAL

...More than 30 years of experience in the cleaning field have made *Alberti International* a world leader in high pressure washers.

Its important and well-known structure , with a direct management and an always helpful and professional staff, makes our company the best partner for all customers.



• **Delayed Total Stop device**

The smallest of the cold models



Dotazione Standard:

- Tubo A/P mt 8
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Pompa con testata in ottone
- Serbatoio detergente

Standard Equipment:

- H./P. hose mt 8
- Gun/Lance
- Low pressure chemical device
- Pump with brass head
- Detergent tank



GEO	150
Pressure	150 bar
Water delivery	480l/h
Motor Revolution	2800rpm
Power Supply	230V-50Hz
Motor Power	3 HP
Dimensions mm	450x390x900
Tank capacity	10lt
Weight	27Kg

FT

PROFESSIONAL LINE
COLD

Excellent efficiency

ALBERTI[®]
INTERNATIONAL

•Delayed Total Stop device



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Serbatoio detergente
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Detergent tank
- Pressure regulation valve



FT	120/10	170/13	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	900l/h	900l/h
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP	7,5 HP	10 HP	10 HP
Dimensions mm	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760
Tank Capacity	16lt	16lt	16lt	16lt	16lt	16lt	16lt
Weight	52 kg	56 Kg	56 Kg	60 Kg	60 Kg	64 Kg	64 Kg

Accessori e optional pag. 19

• **Delayed Total Stop device**

Resistant stainless-steel structure

Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Pressure regulation valve



FLEXI SB	120/10	170/13	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5HP	5,5HP	7,5HP	7,5HP	10 HP	10 HP
Dimensions mm	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760
Weight	52 Kg	56 Kg	56 Kg	60 Kg	60 Kg	64 Kg	64 Kg

SUPER ACTIVA

PROFESSIONAL LINE
COLD

ALBERTI[®]
INTERNATIONAL

Massive power for those who pretend

- **Delayed Total Stop device**
- **By-pass**



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure pump with brass head and ceramic pistons
- Pressure regulation valve

Accessori Optional:

- Avvolgitubo
- Anticalcare
- Ugello rotante
- Kit per idrosabbatura
- Testina sturatubi
- Lancia inox alta pressione



Accessories Optional:

- Hose reel
- Scale preventing device
 - Rotating nozzle
 - Sandblaster
 - Pipe jet nozzle
- High pressure lance in stainless steel material

SUPER ACTIVA	300/21	200/30	400/18	500/15	500/21
<i>Pressure</i>	300 bar	200 bar	400 bar	500 bar	500 bar
<i>Water delivery</i>	21 l/min	30 l/min	18 l/min	15 l/min	21 l/min
<i>Motor Revolution</i>	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
<i>Power Supply</i>	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
<i>Motor Power</i>	16 HP	15 HP	20 HP	20 HP	25 HP
<i>KW</i>	11,8KW	11,02 KW	14,70KW	14,70KW	18,38KW
<i>Dimensions mm</i>	660x1250x900	660x1250x900	660x1250x900	660x1250x900	660x1250x900
<i>Weight</i>	122 Kg	122 Kg	140 Kg	140 Kg	160 Kg

•Delayed Total Stop device

To be fitted anywhere



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in alta pressione (vaschetta opzionale)
- Dispositivo deterg. in bassa e alta pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Valvola di regolazione pressione

Accessori Optional:

- Comando a distanza
- Telaio in acciaio inox
- Avvolgitubo
- Anticalcare
- Ugello rotante
- Kit per idrosabbatura
- Testina sturatubi

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device (tank optional)
- Low and high pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Pressure regulation valve

Accessories Optional:

- Remote Control
- Stainless steel frame
- Hose reel
- Scale preventing device
- Rotating nozzle
- Sandblaster
- Pipe jet nozzle

IDRO-R	120/10	170/13	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5HP	5,5HP	7,5HP	7,5HP	10 HP	10 HP
Dimensions mm	430x400x700	430x400x700	430x400x700	430x400x700	430x400x700	430x400x700	430x400x700
Weight	52 Kg	56Kg	56 Kg	62 Kg	62 Kg	76 Kg	76 Kg

GASOLINE STORM

PROFESSIONAL LINE
COLD

ALBERTI[®]
INTERNATIONAL

With so much enthusiasm the petrol engine model is ready



Dotazione Standard:

- Struttura portante in tubolare montato su quattro ruote con porta-lancia
 - Motore a Benzina
- Pompa alta pressione con testata in ottone e pistoni in ceramica
 - Pressione regolabile
 - Filtro acqua
 - Tubo A/P mt 10
 - Pistola + Lancia
- Dispositivo detergente in bassa pressione
 - Valvola di regolazione pressione

Standard Equipment:

- Base frame tubular structure on four wheels with gun holder
 - Petrol engine
- High pressure pump with brass head and ceramic pistons
 - Water filter
 - H./P. hose mt 10
 - Gun + Lance
- Low pressure chemical device
 - Pressure regulation valve

Accessories Optional:

- Magnetic scale preventing device
 - Rotating Nozzle
 - Sandblaster
 - Pipe jet nozzle

Accessori Optional:

- Anticalcare magnetico
- Ugello rotante
- Kit per idrosabbiatura
- Testina sturatubi

GASOLINE STORM	170/11	200/13	230/15	250/15
<i>Pressure</i>	170 bar	200 bar	230 bar	250 bar
<i>Water delivery</i>	660l/h	780l/h	900l/h	900l/h
<i>Motor Revolution</i>	3400 rpm	3400 rpm	3400 rpm	3400 rpm
<i>Motor Power</i>	6HP	9HP	11HP	13HP
<i>Dimensions mm</i>	580x900x930	580x900x930	580x900x930	580x900x930
<i>Weight</i>	34Kg	45Kg	50Kg	55Kg

LK 100

HOBBY LINE
HOT

Perfect for slight hot water interventions



Dotazione Standard:

- Tubo A/P mt 8
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Caldaia alta temperatura
- Pompa alta pressione

LK 100	
Pressure	100 bar
Water delivery	390 l/h
Max Water Temp.	0-70 °C
Motor Revolution	2800rpm
Power Supply	230V-50Hz
Motor Power	1,8 HP
Dimensions mm	570x390x910
Diesel tank capacity	12 lt
Weight	45 Kg

•Delayed Total Stop device

•Safety valve

K130

SEMI-PROFESSIONAL LINE
HOT

Small size for the Semi-Professional



Standard Equipment:

- H./P. hose mt 8
- Gun+Lance
- Low pressure chemical device
- High temperature boiler
- High pressure pump

K 130	
Pressure	130 bar
Water delivery	480 l/h
Max Water Temp.	0-70 °C
Motor Revolution	2800rpm
Power Supply	230V-50Hz
Motor Power	2,5 HP
Dimensions mm	440x750x720
Diesel tank capacity	14 lt
Weight	62 Kg

SPICE JET

PROFESSIONAL LINE
HOT

ALBERTI[®]
INTERNATIONAL

*Good price and new style,
but professional first*

- Delayed Total Stop device
- Safety valve



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Caldaia in acciaio
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Steel boiler
- High pressure pump with brass head and ceramic pistons
- Pressure regulation valve



SPICEJET	120/10	150/15	200/15
Pressure	120 bar	150 bar	195 bar
Water delivery	600 l/h	900 l/h	900 l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	7,5 HP
Dimensions mm	800x580x900	800x580x900	800x580x900
Diesel tank Capacity	16lt	16lt	16lt
Weight	92Kg	92Kg	98 Kg

- Delayed Total Stop device
- Safety valve

Cheap and high professional machine



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Caldaia in acciaio inox
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Serbatoio detergente
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- Stainless steel boiler
- High pressure pump with brass head and ceramic pistons
- Detergent tank
- Pressure regulation valve

JOLLY	120/10	150/15	200/15
Pressure	120 bar	150 bar	195 bar
Water delivery	600l/h	900l/h	900l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	7,5 HP
Dimensions mm	880x590x730	880x590x730	880x590x730
Diesel tank Capacity	14lt	14lt	14lt
Weight	118 Kg	118 Kg	122 Kg

NEW COMPACT

PROFESSIONAL LINE

HOT

ALBERTI[®]
INTERNATIONAL

Quality performances in a compact style • Delayed Total Stop device

• Safety valve



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in bassa pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Caldaia in acciaio inox
- Spia mancanza gasolio
- Serbatoio detergente
- Valvola di regolazione pressione
- Spia tensione rete

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Stainless steel boiler
- Fuel warning light
- Detergent tank
- Pressure regulation valve
- Voltage warning light

NEW COMPACT	120/10	150/15	170/13	200/15
Pressure	120 bar	150 bar	170 bar	200 bar
Water delivery	600l/h	900l/h	780l/h	900l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C	0-140°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP
Dimensions mm	880x590x730	880x590x730	880x590x730	880x590x730
Diesel Tank Capacity	14lt	14lt	14lt	14lt
Weight	114Kg	118Kg	118Kg	125Kg

- Delayed Total Stop device
- Safety valve

The top of the comfort



Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Fuel warning light
- Micro-leaks control
- 24V controls
- Water tank
- Serbatoio detergente
- Valvola di regolazione pressione

Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in alta pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Spia mancanza gasolio
- Controllo micro perdite
- Comandi a 24V
- Vaschetta acqua
- Detergent tank
- Pressure regulation valve

SUPERLUX	120/10	170/13	150/15	200/15	150/21
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C	0-140°C	0-140°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP	7,5 HP
Dimensions mm	1020x650x860	1020x650x860	1020x650x860	1020x650x860	1020x650x860
Diesel Tank Capacity	14lt	14lt	14lt	14lt	14lt
Weight	122 Kg	128 Kg	128 Kg	135 Kg	135 Kg

NEW STAR JET

PROFESSIONAL LINE

HOT

For those who want the best

ALBERTI
INTERNATIONAL



- Delayed Total Stop device
- Safety valve



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in alta pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Spia mancanza gasolio
- Controllo micro perdite
- Controllo fiamma
- Comandi a 24V
- Filtro gasolio ispezionabile
- Vaschetta acqua
- Possibilità caldaia 21 lt
- Possibilità cofano ABS
- Serbatoio detergente
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Fuel warning light
- Micro-leaks control
- Flame control device
- 24V controls
- Water tank
- Survey fuel filter
- Possibility 21 LT Boiler
- Possibility ABS Cover
- Detergent tank
- Pressure regulation valve

NEW STAR JET	120/10	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
Max Water Temp.	0-150°C	0-150°C	0-150°C	0-150°C	0-150°C	0-150°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	7,5 HP	7,5 HP	10 HP	10 HP
Dimensions mm	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100
Diesel Tank Capacity	16lt	16lt	16lt	16lt	16lt	16lt
Weight	142 Kg	145 Kg	148 Kg	154 Kg	160 Kg	160 Kg

- Delayed Total Stop device
- Safety valve

An innovative stainless steel design for our hot water range



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo deterg. in alta pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Spia mancanza gasolio
- Controllo micro perdite
- Controllo fiamma
- Comandi a 24V
- Filtro gasolio ispezionabile
- Possibilità caldaia 21 lt
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Fuel warning light
- Micro-leaks control
- Flame control device
- 24V controls
- Survey fuel filter
- Possibility 21 LT Boiler
- Pressure regulation valve

ARGENTA	120/10	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
Max Water Temp.	0-150°C	0-150°C	0-150°C	0-150°C	0-150°C	0-150°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	7,5 HP	7,5 HP	10 HP	10 HP
Dimensions mm	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100	1040x700x1100
Diesel Tank Capacity	16lt	16lt	16lt	16lt	16lt	16lt
Weight	142 Kg	145 Kg	148 Kg	154 Kg	160 Kg	160 Kg

IDRO HOT

PROFESSIONAL LINE
HOT

ALBERTI[®]
INTERNATIONAL

Hot power on the wall



- Delayed Total Stop device
- Safety valve



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Disp. deterg. in alta pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Controllo micro perdite
- Controllo fiamma
- Comandi a 24V
- Caldaia in acciaio inox

Accessori Optional:

- Avvolgitubo
- Anticalcare magnetico
- Anticalcare Chimico
- Ugello rotante
- Kit per idrosabbatura
- Testina sturatubi
- Controllo a Distanza
- Telaio in acciaio inox

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Micro-leaks control
- Flame control device
- 24V controls
- Stainless steel boiler

Accessories Optional:

- Hose reel
- Magnetic scale preventing device
- Scale preventing device
- Rotating nozzle
- Sandblaster
- Pipe jet nozzle
- Remote Control
- Stainless Steel Frame

IDRO HOT	120/10	170/13	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C	0-140°C	0-140°C	0-140°C	0-150°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP	7,5 HP	10 HP	10 HP
Dimensions mm	680x580x1050	680x580x1050	680x580x1050	680x580x1050	680x580x1050	680x580x1050	680x580x1050
Weight	122 kg	130 Kg	130 Kg	135 Kg	135 Kg	148 Kg	148 Kg

- Delayed Total Stop device
- Safety valve

Brand new steam system



Dotazione Standard:

- Tubo A/T mt 10
- Lancia termica
- Pistola automatica

Standard Equipment:

- H./T. hose mt 10
- Termic Lance
- Automatic spray Gun

Accessori Optional:

- Pistola a vapore
- Prolunga + attacco rapido

Accessori Optional:

- Steam spray gun
- Quick-fit extension

MEDI VAP	
<i>Alimentazione</i> <i>Power Supply</i>	230V-50 Hz
<i>Controlli</i> <i>Controls</i>	24V
<i>Motore elettrico</i> <i>Electric Motor</i>	180 W
<i>Consumo Acqua</i> <i>Water Consumption</i>	Vapore secco: 0,2 l/min Vapore umido: da 0,5 a 2,0 l/min Dry steam: 0,2 l/min - Wet Steam from 0,5 to 2,0 l/min
<i>Pressione vapore</i> <i>Steam pressure</i>	10 bar max
<i>Goccia Vapore</i> <i>Steam droplet</i>	max 5 micron (dry steam)
<i>Temperatura vapore</i> <i>Steam Temperature</i>	max 160° C per vapore umido (wet steam) max 210° C per vapore secco (dry steam)
<i>Carburante</i> <i>Fuel</i>	Diesel o Etanolo
<i>Consumo gasolio</i> <i>Fuel consumption</i>	4,18 kg/h
<i>Alimentazione acqua</i> <i>Water Supply</i>	Depurata
<i>Dimensioni e peso</i> <i>Dimensions and weight</i>	85 x 54 x H 73 cm 78 Kg

BOILERS

ALBERTI
INTERNATIONAL

Long term Experience



STAINLESS STEEL BOILER,

with bottom in refractory cement and ceramic fiber, air-cooled, coil Ø 17x 22 mms., hot-wiredrawing 3/8 G.

All the boilers are complete with: combustion head, electrodes, fuel nozzle, burner motor, fuel pump with solenoid, fan and high voltage transformer.

Boilers are ready for connection to high and low pressure (high pressure cleaners) and hot water generators.

CALDAIA

con struttura in Acciaio INOX, fondo in cemento refrattario e fibra ceramica, sistema di raffreddamento ad aria, serpentina in acciaio Ø 17x22 mm., trafilato a caldo, doppia spirale, uscita 3/8 G.

Tutte le caldaie sono complete di: testina di combustione, elettrodi, ugello gasolio, motore bruciatore, ventola, pompa gasolio con elettrovalvola e trasformatore alta tensione.

Le caldaie sono pronte per il collegamento ad alta pressione o in bassa pressione (idropultrici) e generatori di acqua calda.

BOILER	10/13	15	15/18	18/21	15	15/18	18/21
Coil length	mt 19	mt 26	mt 30	mt 42	mt 26	mt 30	mt 42
Thermic power	36.000 Kcal/h	42.000 Kcal/h	50.000 Kcal/h	72.000 Kcal/h	42.000 Kcal/h	50.000 Kcal/h	72.000 Kcal/h
Load	10/13 lt/1'	15 lt/1'	15/18 lt/1'	21 lt/1'	15 lt/1'	15/18 lt/1'	21 lt/1'
Fuel nozzle	1 ÷ 1.10	1.35 ÷ 1.50	1.50 ÷ 1.75	1.75 ÷ 2.00	1.35 ÷ 1.50	1.50 ÷ 1.75	1.75 ÷ 2.00
Working pressure	200 bar	200 bar	200 bar	200 bar	500 bar	500 bar	500 bar
Efficiency	88 %	91 %	91 %	91 %	91 %	91 %	91 %
Fuel consumption	4,18 kg/h	5,20 kg/h	5,70 kg/h	6,25 kg/h	5,20 kg/h	5,70 kg/h	6,25 kg/h
Thickness of the Coil	2 mm	2 mm	2 mm	2 mm	3 mm	3 mm	3 mm

● DI SERIE
Standard
Standard
Standard
Estandar

○ NON DOTATO
Not supplied
Pas prévu
Nicht vorgesehen
Non suministrado

▲ OPTIONAL
Optional
Sur demande
Nach Anfrage
Opcional

FLEXI SB	IDRO HOT	IDRO R	FT	NEW STAR	SUPERLUX	NEW COMPACT	SPICELET	ARGENTIA	K 130	LK 100	GEO	
●	●	●	●	●	●	●	●	●	●	●	●	TOTAL STOP / DELAYED TOTAL STOP DEVICE
●	●	●	●	●	●	●	●	●	○	○	○	REGOLAZIONE PRESSIONE / PRESSURE REGULATION VALVE
○	●	○	○	○	●	●	○	●	○	○	○	COMANDI A 24V. / 24 V CONTROLS
○	●	○	○	○	●	●	○	●	○	○	○	SPIA TENSIONE RETE / VOLTAGE WARNING LIGHT
○	○	○	○	▲	○	▲	○	○	○	○	○	COFANO IN ABS / ABS COVER
○	●	○	○	●	●	●	●	●	●	●	○	VALVOLA DI SICUREZZA / SAFETY VALVE
○	●	●	●	○	○	●	○	●	●	○	●	DISP. ASP. DETERGENTE BASSA PRESSIONE / LOW PRESSURE CHEMICAL DEVICE
○	●	○	○	●	●	●	○	●	○	○	○	CALDAIA IN ACCIAIO INOX / STAINLESS STEEL BOILER
○	○	○	▲	●	●	▲	▲	○	○	○	○	FRENI SU RUOTE / BRAKES ON THE WHEELS
○	○	○	●	●	●	○	○	○	▲	○	●	SERBATOIO DETERGENTE / CHEMICAL TANK
○	●	○	○	●	●	○	○	○	○	○	○	SPIA MANCANZA GASOLIO / FUEL WARNING LIGHT
○	▲	▲	○	●	●	○	○	▲	○	○	○	DISP. ASP. DET. ALTA PRESSIONE / HIGH PRESSURE CHEMICAL DEVICE
○	▲	▲	○	●	●	○	○	▲	○	○	○	VASCHETTA ACQUA CON GALLEGGIANTE / WATER TANKS + FLOATING DEVICE
○	▲	○	○	●	●	▲	○	▲	○	○	○	SPIA CONTROLLO MICROPERDITE / MICRO-LEAKS CONTROL
▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	SISTEMA ANTICALCARE MAGNETICO / MAGNETIC SCALE PREVENTING DEVICE
○	●	○	○	●	▲	▲	○	▲	○	○	○	SPIA CONTROLLO FIAMMA / FLAME CONTROL DEVICE
▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	AVVOLGITUBO / HOSE REEL
○	▲	○	○	●	▲	▲	○	▲	○	○	○	FILTRO GASOLIO ISPEZIONABILE / SURVEY FUEL FILTER
○	▲	○	○	▲	▲	○	○	▲	○	○	○	SISTEMA ANTICALCARE ELETTRONICO / ELECTRONIC SCALE PREVENTING DEVICE
▲	▲	▲	○	▲	▲	▲	○	▲	○	○	○	FLUSSOSTATO / FLOW SWITCH
●	○	○	○	○	○	○	○	●	○	○	○	COFANO INOX / STAINLESS STEEL COVER

Accessories Optional



SPAZZOLA ROTANTE

Rotating Brush
Drehbürste
Brosse Rotative
Hidrocepillo rotativo



LANCIA SCHIUMOGENA

Foam lance
Schäumlanze
Canon à mousse
Lanza espumadora



TESTINA AD ANGOLO VARIABILE CON LANCIA

Lance with multireg nozzle
Lanze mit Multiregdüse
Lance avec buse multireg
Lanza con boquilla multireg



KIT PER IDROSABBIATURA

Sandblaster
Sandstrahler
Sableur
Kit para arenador



TESTINA STURATUBI

Pipe jet nozzle
Rohrreinigungsschlauch
Buse deboucheur
Boquilla a reacción



PISTOLA CON PROLUNGA

Gun with extension
Pistole mit Erweiterung
Pistole avec extension
Empuñadura con prolongación



UGELLO ROTANTE

Rotating nozzle
Rotodüse
Buse rotative
Boquilla rotativa



AVVOLGITUBO 20m + SUPPORTO

Hose reel 20m + support
Schlauchaufwicklung
Enrouleur
Enrollatubo 20m con soporte



ANTICALCARE MAGNETICO

Magnetic scale preventing device
Magnetentalker
Dispositif anticalcaire magnétique
Anticalcáreo magnetico



VASCHETTA ANTICALCARE CHIMICO

Scale preventing device
Kalkschutz
Dispositif anticalcaire électronique
Anticalcáreo electrónico



PROLUNGA LANCIA

Lance extension
Lanzeserweiterung
Extension lance
Prolongacion lanza



LANCIA DOPPIA

Double lance
Doppellanze
Lance double
Lanza doble



CONTROLLO FIAMMA

Flame control device
Kontrolllampe für kraftstoffmangel
Dispositif contrôle flamme
Control llama



ALBERTI[®]

INTERNATIONAL

Via Galileo Galilei c.m. | 46020 Motteggiana (Mn) - ITALY
Tel. ++39 0376 510065 - Fax. ++39 0376 510034
www.alberti-international.it
sales@alberti-international.it | info@alberti-international.it

Dealer: